

# Connected Energy® DLC 3150 Direct Load Controller



Connected Energy® DLC 3150 is a smart grid direct load controller (DLC) enabling demand management with precision and verification. It is a single-load controller with two relays designed to manage a commercial multi-stage HVAC system (5.0 - 7.5 tons) via thermostat loop control. Equipped with a Verizon 3G certified radio for high-reliability two-way communications, the DLC 3150 can measure and report the actual load prior to curtailment, providing granular measurement and verification (M&V). It provides detailed metrics including voltage, current, active power and frequency on a near-real time basis.

### Key Features:

- Measurement and Verification (M&V) of actual load curtailed
- Enables adaptive cycling and predictive analytics
- Two-way, near-real time communications
- Single-load controller for commercial multi-stage HVAC systems

## Product Specifications<sup>1</sup>

### Input Power Requirements

- Power Input 240 VAC ± 20% (192-288); 60 Hz
- Power Consumption 10 Watts Maximum at 240 VAC
- Input Conductor 18 Gauge Standard UL 1015  
1/2" Seal Tight Fitting  
600 V, 105 °C (220 °F) Wire Insulation
- Through Current Capability 100 A
- Dual Load Controller Relays 3 A, 24 VAC

### Direct Load Controller Measurements

- 2-Wire or 3-Wire Single-Phase Measurements
- RMS Voltage Range: 192 - 288 VAC RMS  
Accuracy: ±1%
- RMS Current Range: 0 - 60 A RMS  
Accuracy: ±1%
- Frequency Range: 47 - 63 Hz  
Accuracy: ±0.5%
- Active Power Range: 0 - 15.9 kW  
Accuracy: ±2%

### Environmental Specifications

- Operating Temperature -30 °C to +70 °C
- Storage Temperature -40 °C to +85 °C
- Operating Relative Humidity Up to 95% (non-condensing)

### Software

- Embedded smart grid firmware providing distributed intelligence and enabling M&V capabilities

### LED Indications

- Steady Red Active Load Management
- Steady Green Remote Test Function

### Physical Specifications

- Dimensions (H x W x D) 8.4" x 6.4" x 2.9"  
213 x 162 x 73 mm
- Weight 1.2 lbs /0.54 kg
- Enclosure NEMA IV Rated, Raintight Operation  
High-Impact Polycarbonate  
Neoprene Enclosure Gasket

### Certifications/Standards

- UL Listed
- FCC Certified
- Verizon Network Certified
- Surge Withstand Capability: Meets and Exceeds ANSI C37.90a

### Communications

- Standard Dual-band CDMA 800/1900 MHz  
Built in UDP/TCP/IP stack
- Optional Radio Mesh Networks  
3rd Party Radios
- Device Status Reporting User Configurable  
Upon Event/Change in State

1) Specifications are subject to change without notice.